

CHRISTIE JAZZ SERIES

DWU1800-JS / DWU2400-JS / 4K1600-JS / 4K2100-JS

Corporate | Hospitality & tourism | Museums | Places of worship | Rental & staging | Theme parks & attractions

Outstandingly bright with up to 23,750 lumens, impressively light with a chassis that weighs less than 65 lbs (30kg), and incredibly priced.



Five-year warranty for extra peace of mind.

Complete solutions that work for you

Jazz Series seamlessly integrates into a complete Christie® solution with features like onboard Twist™ warping and blending, optional Mystique™ automated camera-based alignment, and compatibility with Christie Intelligent Camera.

Reliability you can trust

Get extra peace of mind with our industry-leading five-year warranty and virtually maintenance-free operation that works for you 24/7.

Key features

- › **Dynamic contrast for lifelike imagery:** Dive into a world of depth and detail with a dynamic contrast ratio of 25,000:1.
- › **Cutting edge, advanced electronics:** Texas Instruments' 0.8" HEP DMD and optical design give you improved color, contrast, and a more efficient cooling system design.
- › **Wide range of lens options:** With nine interchangeable lenses, including ultra-short throw, you can find the lens that works best for your project.
- › **Reliable laser light source:** 20,000 hours in Standard mode and 50,000 hours in ECO1 mode.



CHRISTIE®

Technical specifications		DWU1800-JS / DWU1800A-JS (TAA)	DWU2400-JS / DWU2400A-JS (TAA)
Image	brightness (lumens)	• 17,800 ISO • 15,000 ANSI	• 23,750 ISO • 20,000 ANSI
	color wheel	• 4 segment - 3X speed	
	contrast (nominal)	• Christie RealBlack™ enabled: 4,000,000:1 • Christie RealBlack disabled: 1,500: 1 (Native) • Dynamic contrast: 25,000:1 (Center)	
Display technology	type	• 1 x 0.8" HEP DMD	
	resolution	• WUXGA • 1920 x 1200 (2,304,000 pixels) (16:10)	
Illumination	type	• High efficiency blue laser phosphor	
	performance	• 20,000 hours to 50% brightness at full power mode • 50,000 hours to 50% brightness at ECO1 mode	
Signal Inputs	standard	• HDMI 2.0b x 2 (HDCP 1.4/2.2) • 3G-SDI x 1 (BNC) • Display Port x 1(1.2a) • USB 2.0 x 1 (Type A) • HDBaseT 1.0 (RJ45) x 1	
	signals	• Horizontal and vertical scaling while maintaining aspect ratio (all inputs)	
	3D	• Active shuttered • HDMI 1.4, HDBaseT - frame packing, top/bottom, side-by-side at 1080p at 60Hz frame sequential WUXGA(RB) up to 120 Hz. • 3D sync in (BNC) - for genlocking projectors • 3D sync out (BNC) - for genlocking projectors, or controlling emitter or polarizer	
	pixel clock	• 600MHz	
	scan rates	• Horizontal: 15.375 kHz ~ 135.0 kHz ; Vertical: 23.98 Hz ~ 120 Hz	
Signal Outputs	monitor out (loop-through)	• 3G-SDI x 1 (BNC) • HDMI x 1 (HDMI out)	
Control and networking		• HDBaseT (RJ45 x 1) • RJ45 x 1 (Ethernet Control over wired network connection) • RS232 x 1 • Remote in: 3.5mm stereo female (provides serial communications and power) • DC JACK 12 VDC, 200 mA max	
Warping and blending	mount type	• Christie Twist™	
	optional	• Christie Twist Premium and Twist Pro • Christie Mystique™ automated camera-based alignment	
TAA-compliant		• Yes	
Lenses	mount type	• Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses)	
	lens options	• 0.46:1 UST lens	
	zoom/focus memory	• 0.78-0.9:1 zoom lens • 0.9-1.3:1 zoom lens • 1.3-1.8:1 zoom lens • 1.44-1.8:1 zoom lens • 1.8-2.4:1 zoom lens • 2.4-4.8:1 zoom lens • 4.8-8.64:1 zoom lens • 8.64-12.96 zoom lens	
Accessories	standard	• IR remote with wired remote jack (wire not included) • AC line cord for projector • Product Safety Guide	
	optional	• Christie One Mount Plus (140-117100-XX) • One Mount Extender Rod (121-125109-XX) • Christie One Rigging Frame V2 (140-155102-XX)	• Christie Intelligent Camera (156-155102-XX) • One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) (121-126100-XX)
Power requirements	operating voltage	• Normal mode: 100-240 VAC at 50/60 Hz	• Normal mode: 100-240 VAC at 50/60 Hz • Supports 100-120 VAC at reduced power with 80% brightness level output
	power consumption (25°C, 220V)	• Normal: 930 • Eco1: 760W • Eco2: 530W	• Normal: 1,290W • Eco1: 990W • Eco2: 670W
	operating current	• Normal mode: 4.23A (220-240 VAC) • 8.73A (100-120 VAC)	• Normal mode: 5.86A (220-240 VAC) • 9.27A (100-120 VAC)
	dissipation @ 220V	• Normal: 3,173 BTU/hr • Eco1: 2,593 BTU/hr • Eco2: 1,808 BTU/hr	• Normal: 4,401 BTU/hr • Eco1: 3,378 BTU/hr • Eco2: 2,286 BTU/hr
Audible noise		• Standard: 44dBA (Max.) • Eco2: 40dBA (Max.)	• Standard: 47dBA (Max.) • Eco2: 42dBA (Max.)
Standby power	LAN off	• < 0.3W	
	LAN on	• < 6W	
Physical	size	• (LxWxH) 23.6 x 20.5 x 7.6" (600 x 520 x 193mm) without feet	
	shipping size	• (LxWxH) 38 x 31.30 x 14.6" (965 x 795 x 370mm)	
	weight	• 64.76lbs (29.4kg)	
	shipping weight	• 94.71lbs (43.0kg)	
Operating environment	temperature	• 32-113 F (0-45 C) (0 - 2,500 feet altitude)	
	humidity	• 10-85% non-condensing	
Regulatory		• This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • Contact Christie for timing of certifications: UL/CSA/IEC 60950-1 • FCC Class A • cTUVus • CE • FDA • CCC • KC • PSE • EAC • BIS • VCCI • RCM • Mexico • BSMI	
Warranty		• Five years parts and labor on the projector • Five years or 20,000 hours parts and labor on the illumination system • Contact an authorized Christie representative for full details of our limited warranty	
Special Features		• 21:9 aspect ratio support and customize EDID. • Fade in & fade out control for shutter function • Support 4K3840x2160 and 4096x2160 signal input • Support Control System : Crestron Roomview V2 • PJLink V2 • AMX - Device Discovery	

Technical specifications

4K1600-JS / 4K1600A-JS (TAA)

4K2100-JS / 4K2100A-JS (TAA)

Image	brightness (lumens)	• 16,600 ISO • 14,000 ANSI	• 21,350 ISO • 18,000 ANSI
	color wheel	• 4 segment - 4X speed	
	contrast (nominal)	• Christie RealBlack™ enabled: 4,000,000:1 • Christie RealBlack disabled: 1,500: 1 (Native) • Dynamic contrast: 25,000:1 (Center)	
Display technology	type	• 1 x 0.8" HEP DMD	
	resolution	• 4K UHD+ • 3840 x 2400 (9,216,000 pixels) (16:10)	
Illumination	type	• High efficiency blue laser phosphor	
	performance	• 20,000 hours to 50% brightness at full power mode • 50,000 hours to 50% brightness at ECO1 mode	
Signal Inputs	standard	• HDMI 2.0b x 2 (HDCP 1.4/2.2) • 12G-SDI x 1 (BNC) • Display Port x 1 (1.2a) • USB 2.0 x 1 (Type A) • HDBaseT 3.0 (RJ45) x 1	
	signals	• Horizontal and vertical scaling while maintaining aspect ratio (all inputs)	
	3D	• Active shuttered and passive polarized stereoscopic 3D • HDMI 2.0b, HDBaseT - frame packing, top/bottom, side-by-side 1080P at 60 Hz • frame sequential at WUXGA(RB) up to 120 Hz. • 4K passive 3D 3840 x 2160 at 60 Hz, 4K passive 3D Dual Pipe 3840 x 2160 at L-60 Hz and R-60 Hz • 3D sync in (BNC) - for genlocking projectors • 3D sync out (BNC) - for genlocking projectors, or controlling emitter or polarizer	
	pixel clock	• 600MHz	
	scan rates	• Horizontal: 15.375 kHz ~ 135.0 kHz ; Vertical: 23.98 Hz ~ 120 Hz	
	monitor out (loop-through)	• 12G-SDI x 1 (BNC) • HDMI x 1 (HDMI out)	
Signal Outputs		• 12G-SDI x 1 (BNC) • HDMI x 1 (HDMI out)	
Control and networking		• HDBaseT 3.0 (RJ45 x 1) • RJ45 x 1 (Ethernet Control over wired network connection) • RS232 x 1 • Remote in: 3.5mm stereo female (provides serial communications and power) • DC JACK 12VDC, 200 mA max.	
Warping and blending	mount type	• Christie Twist™	
	optional	• Christie Twist Premium and Twist Pro • Christie Mystique™ automated camera-based alignment	
TAA-compliant		• Yes	
Lenses	mount type	• Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses)	
	lens options	• 0.46:1 UST lens	
	zoom/focus memory	• 0.78-0.9:1 zoom lens • 0.9-1.3:1 zoom lens • 1.3-1.8:1 zoom lens • 1.44-1.8:1 zoom lens • 1.8-2.4:1 zoom lens • 2.4-4.8:1 zoom lens • 4.8-8.64:1 zoom lens • 8.64-12.96 zoom lens	
Accessories	standard	• IR remote with wired remote jack (wire not included) • AC line cord for projector • Product Safety Guide	
	optional	• Christie Intelligent Camera (156-155102-XX) • One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) (121-126100-XX)	• Christie Intelligent Camera (156-155102-XX) • One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) (121-126100-XX)
Power requirements	operating voltage	• Normal mode: 100-240 VAC at 50/60 Hz	• Normal mode: 100-240 VAC at 50/60 Hz • Supports 100-120 VAC at reduced power with 80% brightness level output.
	power consumption (25°C, 220V)	• Normal: 1,020W • Eco1: 840W • Eco2: 580W	• Normal: 1,340W • Eco1: 1,080W • Eco2: 710W
	operating current	• Normal mode: 4.64A (220-240 VAC) • 9.55A (100-120 VAC)	• Normal mode: 6.09A (220-240 VAC) • 10.09A (100-120 VAC)
	dissipation @ 220V	• Normal: 3,480 BTU/hr • Eco1: 2,866 BTU/hr • Eco2: 1,979 BTU/hr	• Normal: 4,572 BTU/hr • Eco1: 3,685 BTU/hr • Eco2: 2,423 BTU/hr
Audible noise		• Standard: 45dBA (Max.) • Eco2: 43dBA (Max.)	• Standard: 49dBA (Max.) • Eco2: 45dBA (Max.)
Standby power	LAN off	• < 0.3W	
	LAN on	• < 6W	
Physical	size	• (LxWxH) 23.6 x 20.5 x 7.6" (600 x 520 x 193mm) without feet	
	shipping size	• (LxWxH) 38 x 31.30 x 14.6" (965 x 795 x 370mm)	
	weight	• 64.76lbs (29.4kg)	
	shipping weight	• 94.71lbs (43.0kg)	
Operating environment	temperature	• 32-113 F (0-45 C) (0 - 2,500 feet altitude)	
	humidity	• 10-85% non-condensing	
Regulatory		• This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • Contact Christie for timing of certifications: UL/CSA/IEC 60950-1 • FCC Class A • cTUVus • CE • FDA • CCC • KC • PSE • EAC • BIS • VCCI • RCM • Mexico • BSMI	
Warranty		• Five years parts and labor on the projector • Five years or 20,000 hours parts and labor on the illumination system • Contact an authorized Christie representative for full details of our limited warranty	
Special Features		• 21:9 aspect ratio support and customize EDID. • Fade in & fade out control for shutter function • High Frame Rate 1080P at 240 Hz • Support Control System : Crestron Roomview V2 • PLink V2 • AMX - Device Discovery	

For the most current specification information, please visit christiedigital.com

Copyright 2024 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
CD5077-Jazz-data-sheet-Nov-24-En

