

ClickShare CSE-800

Wireless presentation and collaboration system for boardrooms and conference rooms



- **Wireless connection to central screen**
- **Enhanced security features**
- **Up to 8 users on-screen simultaneously**
- **Share from laptop, tablet or smartphone**
- **Moderation, blackboarding and annotation**
- **4K DCI**

The CSE-800 was designed to bring the ClickShare experience to boardrooms, high-end meeting rooms, and conference rooms. Introducing a number of unique features, including simultaneous sharing of up to 8 people, automatic & manual moderation, and blackboarding & annotation, the CSE-800 is the most powerful system in the ClickShare family today. The CSE-800 was designed for enterprise rollouts and offers enhanced security features, a wider range of connectivity options – including AirPlay and Google Cast support for non-HDCP content – and central management.

The power of 2

The CSE-800 features two HDMI inputs and outputs. There is a direct connection with legacy equipment and easy integration with conferencing systems, and two 4K DCI displays can be driven by a single base unit. Furthermore, the 2 network connections allow separate and simultaneous connection to multiple networks (e.g. guest and corporate networks), and provide additional security and convenience for users. Allowing up to 8 persons to share content simultaneously, the CSE-800 ensures connectivity to the central screen and encourages collaboration.

The moderation functionality was specifically designed for use in larger rooms, with multiple people sharing at the same time. To prevent the rapid switching of screens, making the content difficult to follow, a moderator can manually select which content appears on screen and when, ensuring a great experience for all attendees. The moderation function can be switched off at any time, returning the system into ClickShare's normal operating mode, with content being shared upon the click of a button. For user convenience, security features

of the CSE-800 can be set to one of three predefined levels, depending on the company's policies and needs.

ClickShare introduces Touch back function and ideation in your boardrooms. Run any application from your laptop and control it from the screen. With a few touches on the screen, open presentations, share mails, start a video. Focus on audience and content instead of on your presentation tool.

The CSE-800 is also one of the building blocks of the Barco Ideation Wall for interactive and collaborative meetings. By simply combining a Barco UniSee LCD video wall, a specifically designed Touch frame for Barco UniSee and a ClickShare CSE-800 which supports annotation, blackboarding and Touch back function out of the box, you create a single, unified experience in your meeting room allowing you to enjoy both the interactivity features that our wireless collaboration solution ClickShare offers and the seamless viewing experience of Barco UniSee, never seen on LCD video walls before.

PRODUCT SPECIFICATIONS**CLICKSHARE CSE-800**

Especificações gerais	
Sistema operacional	Windows 7/8/8.1/10 32 e 64 bit macOS 10.10/10.11/10.12/10.13/10.14 (Mojave) Android v5 e v6 e v7 e v8 e 8.1 (aplicativo do ClickShare) iOS 8, 9, 10, 11 e 12 (aplicativo ClickShare)
Saídas de Vídeo	2x HDMI
Entradas de vídeo	2x HDMI
Resolução de saída	4K DCI (4096 x 2160) a 60 Hz
Compatível com AirPlay	Espelhamento de iOS (AirPlay) do iOS 9.0 até iOS 12/Mac OS 10.14
Suporte para Google Cast	Android 8.1 Oreo
Resoluções de entrada	4K DCI (4096 x 2160) a 60 Hz
Taxa de quadro	Entradas de uso: Até 60 fps com uma entrada em 4K Até 30 fps com duas entradas em 4K Usando o ClickShare Button ou Aplicativos: Até 30 fps
Nível de Ruído	Máx. 25 dBA a 0 a 30°C Máx. 30 dBA a 30 a 40°C
Número de fontes simultâneas na tela	8 (4 por tela)
Número de conexões simultâneas	64
Compatibilidade com iPad, iPhone e Android	Compartilhamento de documentos, navegador, câmera para dispositivos Android e iOS através do aplicativo do ClickShare
Área de trabalho estendida	Disponível (dependendo do seu sistema operacional). Pode exigir Pacote de Extensão do ClickShare.
Protocolo de autenticação	WPA2-PSK em modo individual WPA2-PSK ou IEEE 802.1X usando o ClickShare Button no modo de integração de rede
Protocolo de transmissão sem fio	IEEE 802.11 a/b/g/n e IEEE 802.15.1
Alcance	Ajustável com modulação da força do sinal; máx. 30m (100 ft) entre o ClickShare Button e a ClickShare Base Unit
Faixa de frequência	2,4 GHz e 5 GHz
Conexões	2x Ethernet LAN 2x USB 2.0; 2x USB 3.0 (traseira); 2x USB 3.0 (frente) Saída de linha analógica de áudio no plugue de metal (3,5 mm), S/PDIF digital
Faixa de temperatura	Operação: 0°C a +40°C (+32°F a +104°F) Máx: 35 °C (95 °F) a 3.000 m Armazenamento: -20 °C a +60 °C (-4 °F a +140 °F)
Umidade	Armazenamento: 0 a 90% de umidade relativa, sem condensação Operação: 0% a 85% de umidade relativa, sem condensação
Sistema antifurto	Trava Kensington
Certificações	FCC/CE
Garantia	3 anos como padrão Pode ser estendida para 5 anos
Dimensões da unidade base ClickShare	
Dimensões (AxLxP)	46,2 mm x 282,3 mm x 206,5 mm (excluindo antenas)/1,8" x 11,1" x 8,1" 146,4 mm x 282,3 mm x 206,5 mm (incluindo antenas)/5,8" x 11,1" x 8,1"
Fonte de alimentação	Entrada padrão 110/220 VCA
Consumo de energia	Normal operation: 90W under full usage 52W under normal usage (connect 2 HDMI outputs, connect 1 HDMI input, share with 4 people) ECO mode: 30W Networked standby mode: < 1W Deep standby mode: < 0.5W
Peso	2,2 kg/4,85 lbs

Last updated: 20 Dec 2018Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.