

Pro L1070W WXGA 3LCD Laser Projector



Projectors

Large Venue

Premium, compact large-venue laser projector

Ultra bright — 7,000 lumens color/white brightness¹ from a compact large-venue laser projector

Exceptional widescreen display — native WXGA resolution for widescreen images; provides up to 1 million pixels on screen

Vibrant, true-to-life images — with Epson® 3-chip 3LCD technology

Worry-free operation — solid-state laser light source and air filter provide virtually maintenance-free operation for up to 20,000 hours²

11 interchangeable lens options — with powered lens shift and lens memory, including an ultra short-throw lens with zero offset (standard lens included, ELPLM08)

Lifelike images — high contrast ratio and BT.709 color space for exceptional clarity and detail

Dynamic projection capabilities — advanced built-in Edge Blending, image warping and shape overlay features for a variety of applications; direct playback from USB storage media

Simplified installation features — full 360-degree mounting, wide lens shift, versatile connectivity; inputs including HDBaseT™ and HDMI® (HDCP 2.2)

Customized performance — brightness modes to maximize light source life and provide a consistent brightness level

Multi-projector setup software — free software controls networked projectors and gives access to image warping and Edge Blending



Specifications

Projection System High-aperture Epson 3LCD, 3-chip technology
Projection Method Front/rear/ceiling mount
Driving Method Poly-silicon TFT Active Matrix
Native Resolution WXGA
Resolution on Screen WXGA up to 1.0 million pixels
Pixel Number in Device 1,024,000 pixels (1280 x 800) x 3 chips
Signal Input
 Maximum display resolution 1920 x 1080 (resizing display)
 Display resolution 1280 x 800 pixels
Aspect Ratio Supports 4:3, 16:9, 16:10
Pixel Arrangement Cross stripe
Color Brightness¹ Color Light Output: 7,000 lumens
White Brightness¹ White Light Output: 7,000 lumens
Contrast Ratio 2,500,000:1 (Dynamic Contrast: On)
Brightness Uniformity (typical) 85%
Color Reproduction Up to 1.07 billion colors
Lens Shift Vertical: ±67%; horizontal: ±30%
Keystone Correction
 Vertical: ±45 degrees; horizontal: ±30 degrees
Illumination Technology Laser Phosphor
Light Source Life² (Normal) 20,000 hours

Projection Lens (Standard)

See website for information on optional lenses.

Type Powered shift/focus/zoom

F-number 1.7 – 2.3

Focal Length 24.0 mm – 38.2 mm

Zoom Ratio Optical zoom 1 – 1.6x

Throw Ratio Range 1.44 – 2.32

Other Features

Operating Temperature 32 ° to 113 °F (0 ° to 45 °C)
Power Supply Voltage 100 – 240 V ±10%, 50/60 Hz AC
Power Consumption 361 W (Normal Mode), 263 W (Extended Mode), 2 W (Network Standby), 0.5 W (Energy Saving)
Fan Noise 34 dB (Normal Mode); 32 dB (Medium Mode) 30 dB (Quiet Mode)
Security Cable hole, Kensington lock provision

Interfaces

DVI-D x 1
 HDMI (HDCP 2.2) x 1
 HDBaseT x 1
 5-BNC, VGA x 1
 Audio in: Mini Stereo x 3
 Variable audio out: Mini Stereo x 1
 USB connector Type B x 1: For service only
 USB connector Type A x 1: For wireless LAN, service, content playback
 Monitor out: Mini D-sub 15-pin x 1
 Serial: RS-232c x 1
 Remote Stereo Mini x 1
 Wired LAN: RJ45

Video I/O

Input Signal

Input Video Signal (HDMI, DVI-D and HDBaseT ports)
 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/
 4096 x 2160

Dimensions (W x D x H)

Including Feet, Lens
 21.5" x 7.4" x 19.1" (545 x 189 x 484 mm)

Weight 34.4 lb without lens

Remote Control

Features Power, source search selection, lens shift, zoom, focus, test pattern selection, A/V Mute, freeze, user ID, auto, aspect, color mode, number, page up and down, E-zoom, volume, menu, enter, esc and pointer functions

Operating Angle

Right/left: Front: ± 60 degrees; Rear: ± 30 degrees
 Upper/lower: Front: + 30 to - 20 degrees; Rear: + 50 to + 10 degrees


Operating Distance 98 ft

Support

The Epson ConnectionSM

Pre-sales support U.S. and Canada 800-463-7766
 Internet website www.epson.com

Service Programs The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first. Epson Road Service program with free Next-Business-Day replacement³, PrivateLine[®] dedicated toll-free support (U.S. and Canada only)



Eco Features

RoHS compliant
 Recyclable product⁴
 Epson America, Inc. is a SmartWay[®] Transport Partner⁵

What's in the Box

Pro L1070W projector, a lens, power cable, cable cover, projector remote control with batteries, Quick Setup Sheet

Ordering Information

Pro L1070W	V11H957020
Replacement air filter (ELPAF46)	V13H134A46
Ultra short-throw zoom lens (ELPLX01)	V12H004X01
Ultra short-throw zoom lens (white) (ELPX01W)	V12H004Y01
Short-throw #1 zoom lens (ELPLU03S)	V12H004UA3
Short-throw #2 zoom lens (ELPLU04)	V12H004U04
Wide-throw #1 zoom lens (ELPLW05)	V12H004W05
Wide-throw #2 zoom lens (ELPLW06)	V12H004W06
Wide-throw #3 zoom lens (ELPLW08)	V12H004W08
Middle-throw #1 zoom lens (ELPLM08)	V12H004M08
Middle-throw #2 zoom lens (ELPLM15)	V12H004M0F
Middle-throw #3 zoom lens (ELPLM10)	V12H004M0A
Middle-throw #4 zoom lens (ELPLM11)	V12H004M0B
Long-throw zoom lens (ELPLL08)	V12H004L08
Epson ceiling mount - low ceilings (ELPMB47)	V12H802010
Epson ceiling mount - high ceilings (ELPMB48)	V12H803010
HDBaseT transmitter (ELPHD01)	V12H547020
Wireless LAN module (ELPAP10)	V12H731P02

¹ Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. Some lenses will not support the maximum brightness level of this projector. | ² No required maintenance for the light source and filter up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m3 of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | ³ Expedited shipping not available in all areas. Road Service orders must be in by 3 p.m. Eastern Time for Next-Business-Day delivery. | ⁴ For convenient and reasonable recycling options, visit www.epson.com/recycle | ⁵ SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future[™]
eco.epson.com



Epson America, Inc.
 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark and Epson Connection is a service mark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2020 Epson America, Inc. Com-SS-Oct-13 CPD-58672R1 2/20