

▼ Display/image

Display technology	DLP®
Resolution	UHD (3840x2160)
Brightness	4,000 lumens
Contrast ratio - dynamic	700,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9
Screen size	100" ~ 150" diagonal

▼ Lamp info

Light source type	DuraCore Laser
LASER life	30,000 hours

▼ Optical

Throw ratio	0.25:1
Projection distance	10.53" - 21.43"
Zoom type	Fixed
Native offset	120%

▼ Connectivity

Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 2.0 (eARC), 1 x USB service shared with USB-A power, 1 x DC Outputs 1 x Audio 3.5mm, 1 x 3D sync Control 1 x HDBaseT 4K, 1 x RJ45, 1 x RS232
-------------	---

▼ General

Noise level (min)	29dB
Noise level (max)	34dB
3D	Full 3D
Security	Security bar, Kensington Lock
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C~40°C/32°F~104°F, max. altitude 3,048m/10,000ft, max. humidity operating 80%, non-operating 90%
Remote control	Yes
Speaker count	1
Watts per speaker	15W
In the box	Projector, QSG, Power Adapter and Cable, Remote, Batteries (2xAAA)

▼ Networking

LAN	Yes
-----	-----

▼ Power

Power supply	250W
--------------	------

▼ Weight and dimensions

Dimensions (W x D x H)	12.87" x 12.91" x 3.35"
Net weight	9.92 lbs